

M/M 粗牙機械螺紋 2A Q(60oC)

延昌五金鉤環彈簧工廠

E-MAIL: yenchang201@gmail.com

URL: www.yenchang.com.tw



規格	牙距	外徑		軋造徑	
	P	MAX	MIN	MAX	MIN
M1	0.25	0.980	0.838	0.729	0.693
M1.1	0.25	1.098	0.938	0.829	0.793
M1.2	0.25	1.180	1.140	1.040	1.010
M1.4	0.30	1.380	1.340	1.200	1.160
M1.7	0.35	1.680	1.610	1.460	1.420
M2	0.40	1.980	1.890	1.720	1.690
M2.3	0.40	2.280	2.190	2.020	1.990
M2.5	0.45	2.480	2.380	2.180	2.150
M2.6	0.45	2.580	2.480	2.280	2.250
M3	0.50	2.980	2.880	2.640	2.610
M3.5	0.60	3.470	3.360	3.060	3.030
M4	0.70	3.980	3.840	3.490	3.450
M4.5	0.75	4.470	4.340	3.960	3.920
M5	0.80	4.980	4.830	4.430	4.380
M6	1.00	5.970	5.820	5.300	5.250
M7	1.00	6.970	6.820	6.300	6.250
M8	1.25	7.960	7.790	7.120	7.070
M9	1.25	8.960	8.790	8.120	8.070
M10	1.50	9.960	9.770	9.120	8.910
M11	1.50	10.970	10.730	9.970	9.910
M12	1.75	11.950	11.760	10.790	10.730
M14	2.00	13.950	13.740	12.630	12.560
M16	2.00	15.950	15.740	14.630	14.560
M18	2.50	17.950	17.710	16.310	16.230
M20	2.50	19.950	19.710	18.310	18.230