

# UNC MACHINE SCREW 2A Q(60oC)

YENCHANG HARDWARE HOOK SPRING FACTORY

E-MAIL: [yenchang201@gmail.com](mailto:yenchang201@gmail.com)

URL: [www.yenchang.com.tw](http://www.yenchang.com.tw)



SIZE	TEETH	OUTSIDE DIAMETER		MAJOR DIAMETER	
	T	MAX	MIN	MAX	MIN
#1	64	1.838	1.743	1.570	1.540
#2	56	2.169	2.066	1.860	1.840
#3	48	2.496	2.383	2.140	2.110
#4	40	2.824	2.695	2.400	2.360
#5	40	3.154	3.026	2.720	2.690
#6	32	3.484	3.333	2.950	2.910
#8	32	4.142	3.991	3.600	3.570
#10	24	4.800	4.618	4.090	4.050
#12	24	5.461	5.279	4.750	4.700
1/4	20	6.322	6.117	5.500	5.450
5/16	18	7.907	7.687	6.980	6.930
3/8	16	9.491	9.254	8.450	8.400
7/16	14	11.076	10.816	9.890	9.830
1/2	13	12.661	12.386	11.390	11.320
9/16	12	14.246	13.958	12.870	12.800
5/8	11	15.834	15.528	14.330	14.260
3/4	10	19.004	18.677	17.340	17.270
7/8	9	22.176	21.824	20.340	20.260
1"	8	25.349	24.969	23.280	23.200
1-1/3"	7	28.519	28.103	26.160	26.070
1-1/4"	7	31.694	31.278	29.330	29.240
1-3/8"	7	34.864	34.002	32.120	32.020